



**MAXIMUM OPERATING CONDITIONS**

Temp°C	Pressure	Speed
-30		1.5ft/sec
+100		0.5m/sec

HII	

METRIC	HII	REFER TO SEAL SECTION OF CATALOGUE	L	LI		HII
				1400-1405 1410-1415	1420-1425 1430-1435	
PART No.	$\phi D$	$\phi d$				$\phi ds$
*MDK 8	14	8	2.5	1.3		10.1
*MDK 10	16	10	2.5	1.3		12.1
*MDK 11	17	11	2.5	1.3		13.1
*MDK 12	18	12	2.5	1.3		14.1
*MDK 13	19	13	2.5	1.3		15.1
*MDK 14	20	14	2.5	1.3		16.1
*MDK 15	21	15	2.5	1.3		17.1
MDK 16	22	16	2.5	1.3		18.1
*MDK 17	23	17	2.5	1.3		19.1
MDK 18	24	18	2.5	1.3		20.1
*MDK 20	27.5	20	3	1.6		22.9
*MDK 23	30.5	23	3	1.6		25.9
*MDK 24	31.5	24	3	1.6		26.9
MDK 25	32.5	25	3	1.6		27.9
*MDK 27	34.5	27	3	1.6		29.9
*MDK 28	35.5	28	3	1.6		30.9
MDK 30	37.5	30	3	1.6		32.9
MDK 32	39.5	32	3	1.6		34.9
MDK 32-46-3-9	46	32	9	3		39.5
MDK 33	40.5	33	3	1.6		35.9
MDK 35	42.5	35	3	1.6		37.9
*MDK 36	43.5	36	3	1.6		38.9
*MDK 37	44.5	37	3	1.6		39.9
MDK 40	47.5	40	3	1.6		42.9
MDK 40-52-3-9	52	40	9	3		46
*MDK 43	50.5	43	3	1.6		45.9
*MDK 45	52.5	45	3	1.6		47.9
*MDK 46	56	46	4	2.15		50.6
*MDK 48	58	48	4	2.15		52.6
MDK 50	60	50	4	2.15		54.6
MDK 55	65	55	4	2.15		59.6
*MDK 56	66	56	4	2.15		60.6
*MDK 57	67	57	4	2.15		61.6
MDK 60	70	60	4	2.15		64.6
MDK 63	73	63	4	2.15		67.6
*MDK 65	75	65	4	2.15		69.6
MDK 70	80	70	4	2.15		74.6
*MDK 72	82	72	4	2.15		76.6
MDK 75	85	75	4	2.15		79.6
MDK 78	88	78	4	2.15		82.6
MDK 80	90	80	4	2.15		84.6
MDK 90	100	90	4	2.15		94.6
MDK 100	110	100	4	2.15		104.6
MDK 120	130	120	4	2.15		124.6
MDK 127	137	127	4	2.15		131.6
MDK 140	150	140	4	2.15		144.6

\*Please contact DLI sales team for availability.