



MAXIMUM OPERATING CONDITIONS		
Temp C	Pressure	Speed
-30		
+100		

IMPERIAL			+0 -0.25	+0.05 +0
Part No.	ϕD	ϕd	ϕdR	LG
MRR 34-22-6	34	22	17.6	2.5
MRR 45-35-5	45	35	30.6	3.1
MRR 50-30-6.48	50	30	25.6	3.3
MRR 55-40-6	55	40	35.6	3.1
MRR 55-40-6.48	55	40	35.6	3.1
MRR 60-40-6.48	60	40	35.6	3.3
MRR 65-45-6.48	65	45	40.6	3.3
MRR 65-50-6	65	50	45.6	3.1
MRR 70-50-6.48	70	50	45.6	3.3
MRR 80-60-6.48	80	60	55.6	3.3
MRR 90-70-6.48	90	70	65.6	3.3
MRR 95-75-6.48	95	75	70.6	3.3
MRR 100-80-6.48	100	80	75.6	3.3
MRR 104.5-85-6.48	104.5	85	80.6	3.3
MRR 105-85-6.48	105	85	80.6	3.3
MRR 110-90-6.48	110	90	85.6	3.3
MRR 115-95-6.48	115	95	90.6	3.3
MRR 120-100-6.48	120	100	95.6	3.3
MRR 125-105-6.48	125	105	100.6	3.3
MRR 130-110-6.48	130	110	105.6	3.3